

L-HA-SP

Recessed downlight with inclined beam 20°

LIGHT SOURCE



POWER 15 W



> 90



- ▶ 2700K
- ▶ 3000K
- ▶ 4000K



RGBW not available

OPTIC

Available optics



10-20°



20-35°



35-60°



>60°

Glass

- ▶ Tempered transparent
- ▶ Tempered frosted

Plexiglass

- ▶ Transparent
- ▶ Frosted

FIXTURE

Body material

Aluminum 6082

Body finish

Black thickness oxidation

Frame material

- ▶ AISI316L Stainless steel
- ▶ Aluminum 6082

Frame finish

- ▶ Polishing
- ▶ Anodization
- ▶ Coating

IP Rate

IP67

Fixing system



Frame with screws + threaded cover screws, O-Ring + Bushing on demand

ELECTRICAL FEATURES

Driver

Integrated

Dimmable

PWM (100 – 500Hz)

Voltage

18 - 32Vdc

Protections

- ▶ Reverse polarity
- ▶ 500V Spike
- ▶ Interference

MECHANICAL FEATURES

Dimensions

Ø 121.0 mm – Recess 88.0 mm

Weight

1050 gr

Cut-out

93.5 mm *

* Non-executive measures

Use

Outdoor and Indoor

