











TECH LIGHTS

L-PO-SP

Recessed down or uplight

LIGHT SOURCE	
	POWER 15 W
	> 90
	<ul style="list-style-type: none"> ▶ 2700K ▶ 3000K ▶ 4000K
	RGBW not available

OPTIC	
Available accessories	 Anti-glare screen printing
Available optics	 10-20°  20-35°  35-60°  > 60°
Glass	<ul style="list-style-type: none"> ▶ Tempered transparent ▶ Tempered frosted
Plexiglass	<ul style="list-style-type: none"> ▶ Transparent ▶ Frosted

FIXTURE	
Body material	Aluminum 6082
Body finish	Black thickness oxidation
Frame material	<ul style="list-style-type: none"> ▶ AISI316L Stainless steel ▶ Aluminum 6082
Frame finish	<ul style="list-style-type: none"> ▶ Polished ▶ Anodization ▶ Coating
IP Rate	IP67
Fixing system	 Frame with screws + threaded cover screws, O-Ring + Bushing on demand

ELECTRICAL FEATURES	
Driver	Integrated
Dimmable	PWM (100 – 500Hz)
Voltage	18 - 32Vdc
Protections	<ul style="list-style-type: none"> ▶ Reverse polarity ▶ 500V Spike ▶ Interference

MECHANICAL FEATURES	
Dimensions	Ø 98.0 mm – Recess 90.0 mm
Weight	500 gr
Cut-out	68.0 mm * * Non-executive measures
Use	Outdoor and Indoor

