

# MICRO-AFX-05

Multiple recessed downlight

## LIGHT SOURCE



POWER 5x1 W



> 90



- ▶ 2700K
- ▶ 3000K
- ▶ 4000K



RGBW not available



## OPTIC

Available optics



10-20°



20-35°



35-60°

Glass

Tempered transparent glass

## FIXTURE

Body material	Aluminum 6082
Body finish	Black thickness oxidation
Frame material	<ul style="list-style-type: none"> <li>▶ AISI316L Stainless steel</li> <li>▶ Aluminum 6082</li> <li>▶ Brass</li> </ul>
Frame finish	<ul style="list-style-type: none"> <li>▶ Polishing</li> <li>▶ Anodization</li> <li>▶ Galvanization*</li> <li>▶ Coating</li> </ul> <p style="text-align: right; font-size: small;">*For interiors only</p>
IP Rate	IP67
Fixing system	Springs

## ELECTRICAL FEATURES

Driver	External
Dimmable	PWM (100 – 500Hz)
Voltage	18 - 32Vdc
Protections	<ul style="list-style-type: none"> <li>▶ Reverse polarity</li> <li>▶ 500V Spike</li> <li>▶ Interference</li> </ul>

## MECHANICAL FEATURES

Dimensions	101.5x21.5 mm – Recess 27.5 mm
Weight	80 gr
Cut-out	97.5 mm **
Use	Outdoor and Indoor

\*\* Non-executive measures

