








**ICONIC LIGHTS**

# MICRO-AFX

Shallow recessed downlight



LIGHT SOURCE	
	POWER 1 W
	> 90
	<ul style="list-style-type: none"> <li>▶ 2700K</li> <li>▶ 3000K</li> <li>▶ 4000K</li> </ul>
	RGBW not available

OPTIC	
Available optics	   10-20°    20-35°    35-60°
Glass	Tempered transparent glass

FIXTURE	
Body material	Aluminum 6082
Body finish	Black thickness oxidation
Frame material	<ul style="list-style-type: none"> <li>▶ AISI316L Stainless steel</li> <li>▶ Aluminum 6082</li> <li>▶ Brass</li> </ul>
Frame finish	<ul style="list-style-type: none"> <li>▶ Polishing</li> <li>▶ Anodization</li> <li>▶ Galvanization*</li> <li>▶ Coating</li> </ul> *For interiors only
IP Rate	IP67
Fixing system	Springs, O-Ring + Bushing

ELECTRICAL FEATURES	
Driver	External
Dimmable	PWM (100 – 500Hz)
Voltage	18 - 32Vdc
Protections	<ul style="list-style-type: none"> <li>▶ Reverse polarity</li> <li>▶ 500V Spike</li> <li>▶ Interference</li> </ul>

MECHANICAL FEATURES	
Dimensions	Ø 21.5 mm – Recess 27.5 mm
Weight	20 gr
Cut-out	17.5 mm **      ** Non-executive measures
Use	Outdoor and Indoor

