

ICONIC LIGHTS

MICRO-MC

Shallow recessed concave trim downlight

LIGHT SOURCE



POWER 1 W



> 90



- ▶ 2700K
- ▶ 3000K
- ▶ 4000K



RGBW not available

OPTIC

Available optics



10-20°



20-35°



35-60°


Glass

Tempered transparent glass




FIXTURE

Body material	Aluminum 6082
Body finish	Black thickness oxidation
Frame material	<ul style="list-style-type: none"> ▶ AISI316L Stainless steel ▶ Aluminum 6082 ▶ Brass
Frame finish	<ul style="list-style-type: none"> ▶ Polishing ▶ Anodization ▶ Galvanization* ▶ Coating <p style="text-align: right; font-size: small;">*For interiors only</p>
IP Rate	IP67
Fixing system	Springs, O-Ring + Bushing



ELECTRICAL FEATURES

Driver	External
Dimmable	PWM (100 – 500Hz)
Voltage	18 - 32Vdc
Protections	<ul style="list-style-type: none"> ▶ Reverse polarity ▶ 500V Spike ▶ Interference



MECHANICAL FEATURES

Dimensions	Ø 21.5 mm – Recess 27.5 mm
Weight	20 gr
Cut-out	17.5 mm * * Non-executive measures
Use	Outdoor and Indoor