

S-AFX

Recessed downlight

LIGHT SOURCE



POWER 3 W



> 90



- ▶ 2700K
- ▶ 3000K
- ▶ 4000K



RGBW not available

OPTIC

Available accessories



Honeycomb louvre



Black reflector for specific wall washer effect

Available optics



10-20°



20-35°



35-60°

Glass

Tempered transparent glass

FIXTURE

Body material	Aluminum 6082
Body finish	Black thickness oxidation
Frame material	<ul style="list-style-type: none"> ▶ AISI316L Stainless steel ▶ Aluminum 6082 ▶ Brass
Frame finish	<ul style="list-style-type: none"> ▶ Polishing ▶ Anodization ▶ Galvanization* ▶ Coating <p style="text-align: right; font-size: small;">*For interiors only</p>
IP Rate	IP67
Fixing system	Springs, O-Ring + Bushing

ELECTRICAL FEATURES

Driver	Integrated
Dimmable	PWM (100 – 500Hz)
Voltage	18 - 32Vdc
Protections	<ul style="list-style-type: none"> ▶ Reverse polarity ▶ 500V Spike ▶ Interference

MECHANICAL FEATURES

Dimensions	Ø 45.0 mm – Recess 52.0 mm
Weight	80 gr
Cut-out	34.5 mm ** ** Non-executive measures
Use	Outdoor and Indoor

